

**Industrial Ethernet
IE-PS-V04P-2SC-MM-BP**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



PushPull plug-in connector set according to IEC
61076-3-106 ver.4 (IEC24702), plastic with SC insert

General ordering data

Type	IE-PS-V04P-2SC-MM-BP
Order No.	1963370000
Version	FO connector, Variant 4, SC-Duplex multi-mode, with kink prevention, IP 67
GTIN (EAN)	4032248651849
Qty.	10 pc(s).

Data sheet

**Industrial Ethernet
IE-PS-V04P-2SC-MM-BP**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 56.2 g

Temperatures

Operating temperature -40 °C...70 °C Storage temperature
 Installation temperature

Downloads

GOST Approval POCC
 DE.ME25.B01411.pdf

General data

Colour	Miscellaneous	Connection 1	SC
Connection 2		Description of article	Variant 4, SC-Duplex multi-mode, with kink prevention
Fibre type	SC	Housing main material	PA UL 94 V0
Insertion loss	Multimode	Plugging cycles	500
Protection degree	0.5 dB singlemode; 0.4 dB multimode; 1.5 dB POF	Return loss (attenuation)	40 dB singlemode; 30 dB multimode
Sheath diameter, max.	IP 67	Sheath diameter, min.	5 mm
	10 mm		

Standards

Connector standard IEC 61076-3-106 Var. 4,
 IEC 61754-24

Classifications

ETIM 3.0	EC001121	ETIM 4.0	EC002641
ETIM 5.0	EC002641	ETIM 6.0	EC002641
UNSPSC	30-21-18-10	eClass 5.1	27-26-07-08
eClass 6.2	27-26-07-08	eClass 7.1	27-25-05-04

Approvals

Approvals



ROHS Conform

Data sheet

**Industrial Ethernet
IE-PS-V04P-2SC-MM-BP**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Dimensioned drawing

