

## TINA2-O

~35° 15° oval beam optimized for CREE XP-E.  
Assembly with holder and installation tape.


### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 16.1 mm
Height	9.7 mm
Fastening	tape
Colour	black
Box size	451 x 241 x 298 mm
Box weight	8.3 kg
Quantity in Box	4140 pcs
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
TINA2-XP-O	Lens	PMMA	clear
TINA2-XP-HLD-TAPE-BLK	Holder	PC	black
TINA-TAPE3	Tape	PU tape	black




INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	C11418	TINA2-XP-HLD-TAPE-BLK	PC	black
2	C11050	TINA2-XP-O	PMMA	

Tolerances if not otherwise shown  
According to DIN ISO 2768-1  
Linear measures:  
Up to 30mm class M, otherwise class C.  
According to DIN ISO 2768-2  
Form and position: class L

**LEDiL**

Ledil Oy  
Salorankatu 10  
FIN 24240 SALO  
Finland

THIRD ANGLE PROJECTION: 

DRAWING TITLE

CA11052\_TINA2-O

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

SIZE PART NUMBER

A4


CA11052

SCALE 3:1 WEIGHT 1,3 g SHEET 1/1


### PHOTOMETRIC DATA (MEASURED):




LED XP-E  
FWHM 32.0 + 14.0°  
Efficiency 87 %  
Peak intensity 4.400 cd/lm  
Required components:




LED XP-E-HEW  
FWHM 34.0 + 16.0°  
Efficiency %  
Peak intensity 3.360 cd/lm  
Required components:



LED XP-E2  
FWHM 34.0 + 14.0°  
Efficiency 86 %  
Peak intensity 5.100 cd/lm  
Required components:





LED XP-G  
FWHM 35.0 + 16.0°  
Efficiency 87 %  
Peak intensity 3.900 cd/lm  
Required components:




#### PHOTOMETRIC DATA (MEASURED):




LED XP-G2  
 FWHM 34.0 + 16.0°  
 Efficiency 87 %  
 Peak intensity 4.000 cd/lm  
 Required components:





LED XT-E  
 FWHM 35.0 + 16.0°  
 Efficiency 85 %  
 Peak intensity 3.800 cd/lm  
 Required components:



LED H35B0 (LEMWA32)  
 FWHM 35.0 + 15.0°  
 Efficiency 86 %  
 Peak intensity 4.200 cd/lm  
 Required components:





LED H35C0 (LEMWA33)  
 FWHM 33.0 + 17.0°  
 Efficiency 86 %  
 Peak intensity 3.500 cd/lm  
 Required components:



### PHOTOMETRIC DATA (MEASURED):



#### LG Innotek

LED H35C1 (LEMWA33)  
FWHM 35.0 + 17.0°  
Efficiency 85 %  
Peak intensity 3.900 cd/lm  
Required components:




#### SAMSUNG

LED LH181A  
FWHM 33.0 + 17.0°  
Efficiency 72 %  
Peak intensity 3.100 cd/lm  
Required components:



### PHOTOMETRIC DATA (SIMULATED):



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)