

## Surge protection device - S-PT-EX(I)-24DC-3/4" - 2882585

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Surge protection in the IP67 screw-on module for measuring sensors in intrinsically safe circuits, direct mounting with 3/4" NPT outer thread, cable gland for the signal cable, two-stage protective circuit. HART-compatible.

### Why buy this product

- Arresters in hexagonal pipe with various outer threads



### Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	440.000 g
Custom tariff number	85363010
Country of origin	Germany

### Technical data

#### Dimensions

Height	34 mm
Width	34 mm
Depth	148 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 50 °C
Degree of protection	IP67

#### General

Housing material	Zinc die-cast
Flammability rating according to UL 94	V-0
Color	silver

## Surge protection device - S-PT-EX(I)-24DC-3/4" - 2882585

### Technical data

#### General

Standards for clearances and creepage distances	IEC 60664-1
	EN 60079-0
	EN 60079-11
Mounting type	ct screw connection
Type	Screw-in module
Number of positions	3
Direction of action	Line-Line & Line-Earth Ground

#### Protective circuit

IEC test classification	C1
	C2
	C3
	D1
Nominal voltage $U_N$	24 V DC
Maximum continuous voltage $U_C$	30 V DC
	21 V AC
Rated current	350 mA (50 °C)
Operating effective current $I_C$ at $U_C$	$\leq 10 \mu\text{A}$
Residual current $I_{PE}$	$\leq 2 \mu\text{A}$
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (Core-Core)	10 kA
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (Core-Earth)	10 kA
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (Shield-Earth)	10 kA (optional)
Pulse discharge current $I_{imp}$ (10/350) $\mu\text{s}$	1 kA
Max. discharge current $I_{max}$ (8/20) $\mu\text{s}$ maximum (Core-Core)	10 kA
Max. discharge current $I_{max}$ (8/20) $\mu\text{s}$ maximum (Core-Earth)	10 kA
Max. discharge current $I_{max}$ (8/20) $\mu\text{s}$ maximum (Shield-Earth)	10 kA
Nominal pulse current $I_{an}$ (10/1000) $\mu\text{s}$ (Core-Core)	30 A
Nominal pulse current $I_{an}$ (10/1000) $\mu\text{s}$ (Core-Earth)	100 A
Nominal pulse current $I_{an}$ (10/1000) $\mu\text{s}$ (Shield-Earth)	100 A
Output voltage limitation at 1 kV/ $\mu\text{s}$ (Core-Core) spike	$\leq 50 \text{ V}$
Output voltage limitation at 1 kV/ $\mu\text{s}$ (Core-Earth) spike	$\leq 1.4 \text{ kV}$ (Direct grounding)
Output voltage limitation at 1 kV/ $\mu\text{s}$ (Shield-Earth) spike	$\leq 600 \text{ V}$ (optional)
Output voltage limitation at 1 kV/ $\mu\text{s}$ (Core-Core) static	$\leq 50 \text{ V}$
Output voltage limitation at 1 kV/ $\mu\text{s}$ (Core-Earth) static	$\leq 1.4 \text{ kV}$ (Direct grounding)
Residual voltage at $I_n$ (conductor-conductor)	$\leq 50 \text{ V}$
Residual voltage with $I_{an}$ (10/1000) $\mu\text{s}$ (conductor-conductor)	$\leq 50 \text{ V}$
Voltage protection level $U_p$ (core-core)	$\leq 55 \text{ V}$ (C2 -5 kA)

## Surge protection device - S-PT-EX(I)-24DC-3/4" - 2882585

### Technical data

#### Protective circuit

	≤ 50 V (C1 - 250 A)
	≤ 50 V (C3 - 25 A)
	≤ 80 V (D1 - 1 kA)
Voltage protection level $U_p$ (core-ground)	≤ 1.4 kV (C2 -5 kA, direct grounding)
	≤ 1.4 kV (C1 - 500 A)
	≤ 1.4 kV (C3 - 100 A)
	≤ 1.4 kV (D1 - 1 kA)
Voltage protection level $U_p$ (shield-ground)	≤ 650 V (C2 -5 kA optional)
Response time $t_A$ (Core-Core)	≤ 1 ns
Response time $t_A$ (Core-Earth)	≤ 100 ns
Response time $t_A$ (Shield-Earth)	≤ 100 ns
Input attenuation aE, sym.	typ. 0.5 dB (≤ 1 MHz / 50 Ω)
	typ. 0.2 dB (Up to 400 kHz, 150 Ω)
Cut-off frequency $f_g$ (3 dB), sym. in 50 Ohm system	typ. 6 MHz
Cut-off frequency $f_g$ (3 dB), sym. in 150 Ohm system	typ. 2.5 MHz
Resistance in series	2.2 Ω ±10 %
Surge protection fault message	None
Impulse durability (conductor-conductor)	C2 - 10 kV/5 kA
	D1 - 1 kA
Impulse durability (conductor-ground)	C2 - 10 kV/5 kA
	D1 - 1 kA
Impulse durability (shield-ground)	C2 - 10 kV / 5 kA
	D1 - 1 kA
Alternating current carrying capacity (conductor-ground)	10 A - 1 s
Alternating current carrying capacity (shield-ground)	10 A - 1 s

#### Connection data

Connection name	Input/output
Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Connection line
Connection method	Screw connection
Screw thread	M3
Tightening torque	0.6 Nm
Stripping length	6 mm
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section solid	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	26 ... 16

# Surge protection device - S-PT-EX(I)-24DC-3/4" - 2882585

## Technical data

### Standards and Regulations

Standards/regulations	DIN EN 61643-21
	EN 60079-0
	EN 60079-11
	EN 60079-26
Standards/specifications	EN 61643-21/A2 2013
	EN 60079-0 2012
	EN 60079-11 2012
	EN 60079-26 2007
	IEC 60079-0 2011
	IEC 60079-11 2011
	IEC 60079-26 2006

### General


Maximum inner capacitance $C_i$	2 nF
Maximum inner inductance $L_i$	1 $\mu$ H
Max. input current $I_i$	350 mA ( $T4, T5, T6/\leq 50^\circ\text{C}$ )
Max. input voltage $U_i$	30 V
Maximum input power $P_i$	3 W

### Conformity / approvals


ATEX	# II 1G Ex ia IIC T4...T6 Ga
IECEX	Ex ia IIC T4...T6 Ga

## Drawings

Dimensional drawing



Circuit diagram



# Surge protection device - S-PT-EX(I)-24DC-3/4" - 2882585

## Classifications

### eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807
eCl@ss 9.0	27130807

### ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

### UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

## Approvals

### Approvals

---

Approvals

EAC / EAC

---

Ex Approvals

IECEX / ATEX / INMETRO

---

### Approval details

EAC EAC-Zulassung
-------------------

## Surge protection device - S-PT-EX(I)-24DC-3/4" - 2882585

### Approvals

EAC 7500651.22.01.00243
-------------------------

---