

**MODEL: AMD-12V030WxyA****Summary**

The AMD-12V030WxyA is the Medical Adapter from one of the world's largest power supply manufacturers -Delta.

The product offers a regulated output voltage of 12V, along with wide temperature range from 0°C to +40°C and a minimum holdup time of 15ms.

The state-of-the-art design is made to withstand medical equipment requirements. The rugged, ultra-compact plastic case with shock and vibration resistances.

**Features:**

- 30Watts Output Power.
- 100-240Vac Universal Input.
- AC Receptacle with C8 & C14 option (IEC320AC receptacle)
- Efficiency > 83.5%
- No load power consumption < 0.3W
- Energy star Compliant (Level V)
- Low leakage current
- Brownout & Brownout Recovery
- Medical safety standard compliant UL60601-11/EN60601-1/CSA60601-1
- MTBF: > 600,000 Hrs.

The 30 watts Medical power supply provides overvoltage, overload and over temperature protection.

Due to the wide input voltage range from 90 to 264Vac (Nominal input: 100Vac to 240 Vac), the Delta's medical power supply is worldwide usable.

The Input Socket & output connector are made for easy installation.



## Technical Data

30W Medical Adapter	
<b>Input Data (1)</b>	
Nominal input voltage (wide-range input)	100V-240VAC
Input Voltage range	90V-264VAC
Frequency	47-63 Hz
Max Input Current	0.65A max @ 115VAC, 0.40A max @ 230VAC
Inrush current limitation. I <sup>2</sup> t (+25 °C) typ.	25A @ 115VAC & 50A @ 230VAC
Efficiency (at 115VAC and nominal values)	> 83.5%
No load power consumption	< 0.3W
Mains buffering at nominal load (typ.)	15 msec min @ 115VAC
Turn-on time after applying the mains voltage	3Sec
Transient surge voltage protection	VARISTOR
Input fuse, internal (device protection)	T 3.15 AH / 250VAC
Discharge current to PE	< 0.25mA
Altitude	3,000 m.
<b>Output Data (2)</b>	
Nominal output voltage U <sub>N</sub> / tolerance	12V ± 2%
Setting range of the output voltage	11.7V-12.3V
Nominal output current I <sub>N</sub> convection cooling	2.5A
Max. power dissipation idling/nominal load approx.	30W
Ripple/ Noise (20 MHz)	<120mVpp @ +25 °C
Line Regulation	± 0.5%
Load Regulation :	Exclude output cord : ± 1% Include output cord ± 5%
Protection :	Over Current (Auto Recovery) Over Voltage (Latch) Over Temperature (Latch)
<b>Certification/Standards</b>	
Electrical safety (of information technology equipment)	UR/cUR As per STD UL60601-1/CSA60601-1, CB scheme to EN/IEC60601-1, NEMKO EN60601-1, CE Mark LVD and EMC
<b>RoHS Compliant</b>	<b>Yes</b>



General Data	
MTBF	> 600,000 Hrs
Type of housing	Plastic Enclosed , 94V-1 Polycarbonate, Black
Dimensions (W / H / D)	62 * 30 * 110 mm
Weight	220 g. (reference)
Climatic Data	
Ambient temperature (Operating)	0 °C to 40 °C
Ambient temperature (Storage)	-35 °C to + 85 °C
Humidity	5% to 95% non-condensing
In conformance with EMC guideline 89/336/EEC and low voltage directive 73/23/EEC	FCC (Title 47 Part 15 Class B), EN55022 (CISPR 22 Class B)
EMC (electromagnetic compatibility)	
Immunity to interference according to EN 61000-6-1	
<ul style="list-style-type: none"> <li>EN 61000-4-2<sup>2)</sup> Discharge of static electricity (ESD)</li> </ul>	Housing Contact discharge: Level 4 8 kV Air Discharge : 15 kV
<ul style="list-style-type: none"> <li>EN 61000-4-3<sup>1)</sup> Electromagnetic HF field</li> </ul>	Housing Frequency/Field intensity: Level 3 80Hz – 1GHz / 10V/M, with 1kHz tone/80% modulation
<ul style="list-style-type: none"> <li>EN 61000-4-4<sup>2)</sup> Fast transients (Burst):</li> </ul>	Input L,N,PE : Level 3 2kV <sup>3)</sup> Signal: -
<ul style="list-style-type: none"> <li>EN 61000-4-5<sup>2)</sup> Surge voltage capacities (Surge):</li> </ul>	Input : Level 3 Common Mode : 2kV <sup>3)</sup> Differential Mode : 1kV <sup>4)</sup>
<ul style="list-style-type: none"> <li>EN 61000-4-6<sup>1)</sup> Conducted disturbance</li> </ul>	I/O: Level 3 Frequency / U <sub>o</sub> : 0.15MHz - 80MHz / 10Vrms.
<ul style="list-style-type: none"> <li>EN 61000-4-11<sup>2)</sup> Voltage dips</li> </ul>	Self recoverable, No damage
Noise emission according to EN 61000-6-3	
<ul style="list-style-type: none"> <li>Emitted radio interface</li> <li>Radio interference voltage</li> </ul>	EN55011 (EN55022) CLASS B <sup>5)</sup> EN55011 (EN55022) CLASS B <sup>5)</sup>
<b>EN55011 corresponds to CISPR11 / EN55022 corresponds to CISPR22 / EM 61000 corresponds to IEC 1000</b>	
1) Criterion A: Normal operating behavior within the defined limits. 2) Criterion B: Temporary impairment to operational behavior that is corrected by the device itself. 3) Symmetrical: Conductor to conductor. 4) Asymmetrical: Conductor to ground. 5) Class B: Area of application industry and residential	

## Numbering for Medical Adapter

For example: **AMD-12V030WxyA**

**XX** X XXXX XXXX X XX

**XX**.....**Product Type**

AM	Medical Adapter
----	-----------------

XX **X** XXXX XXXX X XX

**X**.....**Model**

D	Desktop
---	---------

XX X **XXXX** XXXX X XX

**XXXX**.....**Voltage**

12V	12 Voltage
-----	------------

XX X XXXX **XXXX** X XX

**XXXX**.....**Watt**

030W	30 Watt
060W	60 Watt
080W	80 Watt

XX X XXXX XXXX **X** XX

**X**.....**Input Configuration**

2	2 PIN AC
3	3 PIN AC

XX X XXXX XXXX X **X** X

**X**.....**Connector Type**

A	Inner diameter 2,5 mm
B	Inner diameter 2,1 mm

\*\*\* **Outer Diameter 5,5 mm.**

XX X XXXX XXXX XX **X**

**X**.....**Variation**

(Eg, Customer, material,Etc.)

A	Delta Standard -product
---	-------------------------------

# Mechanical drawing

