


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00542	Connector, dc plug, 5.5x2.5x23 mm, molding style, spring contacts, nickel plated, 105° C	1	
2	50-00543	Connector, dc jack, 5.5x2.5x17.6 mm, molding style, spring contacts, nickel plated, 105° C	1	
3	30-00795	Wire, 2C TS, 18 AWG, UL2651, 300V, 105C, 4.4 mm, VW-1, PVC, red and black	1	
4	24-00003	Overmold, PVC	1	black, 105° C, 94V-0
5	24-00004	Overmold, PVC	1	black, 105° C, 94V-0



Wiring Diagram		
50-00542	wire color	50-00543
center	red	center
sleeve	black	sleeve

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	12/6/2016	Initial release	Verified:	RoHS and REACH compliant	
			Dimensions are in millimeters.	Function test: no open, no short circuit, no intermittent	
			Tolerances:	Description:	
			X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, 5.5x2.5x12 mm 50-00542 dc plug to 5.5x2.5 50-00543 jack, 18 AWG, 30-00795 R-B, 105°C	
Scale: 1:1		Part number: 10-02323		Sheet 1 of 1	