



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: x.x = ± 0.4mm  
x.xx = ± 0.25mm
3. RATING: 3A 30VDC
4. TERMINALS: COPPER, SILVER PLATED
- ▲ 5. TRAVEL: FULL TRAVEL 3.2 ± .3mm  
SWITCH to MAKE: 1.8 ± .3mm
6. FUNCTION: OFF-(ON) (MOMENTARY)
7. ELECTRICAL LIFE: 6,000 CYCLES
8. OPERATING TEMPERATURE: -5°C to 60°C
9. CONTACT RESISTANCE: 30mΩ MAX.
10. INSULATION RESISTANCE: 500MΩ MIN@ 500V
11. ▲ DENOTES CRITICAL PARAMETER.
12. 2011/65/EU (RoHS) COMPLIANT.



|                 |                |       |             |       |
|-----------------|----------------|-------|-------------|-------|
| TITLE PB4000AQX |                |       |             |       |
| SCALE 2:1       | DATE 11/8/2017 | DR MW | DWG T004003 | REV A |

|     |        |             |         |    |
|-----|--------|-------------|---------|----|
| A   | 23055  | New Release | 11/8/17 | MW |
| REV | PCR NO | DESCRIPTION | DATE    | BY |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED