

Specification Sheet

Part Number: 126-00043



Arrowhead Push-Mount Cable Tie, 6"L, 50lb, 0.04"–0.14" Panel Thickness, PA66, Natural, 100/pkg

Article Number	126-00043
Type	T50SSF
Color	Natural (NA)
Features & Benefits	<ul style="list-style-type: none">• Quick and easy mounting will save time.• Tie is releasable and reusable providing a cost savings.• Design provides low insertion and high extraction force.
Quantity Per	bag
Product Description	Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.
Short Description	Arrowhead Push-Mount Cable Tie, 6"L, 50lb, 0.04"–0.14" Panel Thickness, PA66, Natural, 100/pkg

Global Part Name

T50SSF-PA66-NA

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

6.25

Length L (Metric)

159.0

Fixation Method

Arrowhead

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.19

Width W (Metric)

4.7

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

1.4

Bundle Diameter Max (Metric)

35.0

Height H (Imperial)

.30

Height H (Metric)	7.50
Panel Thickness Min(Imperial)	0.039
Panel Thickness Max(Imperial)	0.14
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	3.56
Mounting Hole Diameter D (Imperial)	0.25 " - 0.28
Mounting Hole Diameter D (Metric)	6.4 - 7.1 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.1
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987